

01/11/2024

**Kit Components**

Product code	Description
<b>G8472</b>	<b>HaloTag® Alexa Fluor® 660 Ligand</b>
Components:	
G847A	HaloTag® Alexa Fluor® 660 Ligand



**Safety Data Sheet**  
*acc. to OSHA HCS*

Printing date 01/11/2024

Reviewed on 01/10/2024

**1 Identification****Product identifier****Trade name:** HaloTag® Alexa Fluor® 660 Ligand**Article number:** G847A**Application of the substance / the mixture** For Laboratory Use**Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

Promega Corporation

2800 Woods Hollow Road

Madison, WI 53711

U.S.A.

1-800-356-9526 or (608)-274-4330

**Information department:** SDS author: [chemicalregulatory@promega.com](mailto:chemicalregulatory@promega.com)**Emergency telephone number:**

For Chemical Emergency Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300

Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

**2 Hazard(s) identification****Classification of the substance or mixture**

GHS07

Acute Toxicity - Oral 4 H302 Harmful if swallowed.

Acute Toxicity - Dermal 4 H312 Harmful in contact with skin.

**Label elements****GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).**Hazard pictograms**

GHS07

**Signal word** Warning**Hazard-determining components of labeling:**

dimethyl sulfoxide

**Hazard statements**

Harmful if swallowed or in contact with skin.

**Precautionary statements**

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves / protective clothing.

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/11/2024

Reviewed on 01/10/2024

Trade name: HaloTag® Alexa Fluor® 660 Ligand

(Contd. of page 1)

*If swallowed: Call a poison center/doctor if you feel unwell.**If on skin: Wash with plenty of water.**Rinse mouth.**Take off contaminated clothing and wash it before reuse.**Dispose of contents/container in accordance with local/regional/national/international regulations.***Classification system:****NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 0

Reactivity = 0

**HMIS-ratings (scale 0 - 4)**

Health = 1

Fire = 0

Reactivity = 0

**OSHA Hazard Overview (Criteria according to 29CFR1910.1200):** Not applicable**Primary route(s) of entry:**

Dermal

Oral

**Target Organ(s):**

Dermal hazard (Cutaneous hazard)

Risk of damage to eyes

**Other hazards****Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

## 3 Composition/information on ingredients

**CAS No. Description**

HaloTag Alexa Fluor 660

**Chemical characterization: Mixtures****Description:**

The product is made up of a mixture of hazardous and non-hazardous components. The exact concentration percentages and components name may be withheld as a Promega Corp. trade secret.

**Dangerous components:**

67-68-5 dimethyl sulfoxide

75-100%

**Additional information:** For the wording of the listed risk phrases refer to section 15.

## 4 First-aid measures

**Description of first aid measures****General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

**After inhalation:** If the patient feels unwell or is concerned, obtain medical advice.**After skin contact:** Immediately wash with water and soap and rinse thoroughly.**After eye contact:** Rinse opened eye for several minutes under running water.**After swallowing:** Seek immediate medical advice.

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/11/2024

Reviewed on 01/10/2024

**Trade name:** HaloTag® Alexa Fluor® 660 Ligand

(Contd. of page 2)

**Information for doctor:**

**Most important symptoms and effects, both acute and delayed**

None

No further relevant information available.

**Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

## 5 Fire-fighting measures

**Extinguishing media**

**Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**Special hazards arising from the substance or mixture**

None known

No further relevant information available.

**Advice for firefighters** No special advice.

## 6 Accidental release measures

**Personal precautions, protective equipment and emergency procedures**

Remove persons from danger area.

Wear protective clothing.

**Environmental precautions:**

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

**Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

**Reference to other sections**

See Section 7 for information on safe handling.

See Section 13 for disposal information.

## 7 Handling and storage

**Handling:**

**Precautions for safe handling** No special precautions are necessary if used correctly.

**Information about protection against explosions and fires:** The product is not flammable.

**Conditions for safe storage, including any incompatibilities**

**Storage:**

**Requirements to be met by storerooms and receptacles:** Do not store below -20°C. Protected from light.

**Information about storage in one common storage facility:** Not required.

**Further information about storage conditions:** None.

**Specific end use(s)** No further relevant information available.

US

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/11/2024

Reviewed on 01/10/2024

Trade name: HaloTag® Alexa Fluor® 660 Ligand

(Contd. of page 3)

## 8 Exposure controls/personal protection

### Control parameters

**Components with limit values that require monitoring at the workplace:**

**67-68-5 dimethyl sulfoxide**

**WEEL** Long-term value: 250 ppm

**Additional information:** The lists that were valid during the creation were used as basis.

### Exposure controls

#### Personal protective equipment:

#### General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Clean skin thoroughly immediately after handling the product.

**Breathing equipment:** Not required.

**Protection of hands:** Not required.

#### Material of gloves

Gloves impermeable to the specific chemical substance.

Please observe the instructions regarding permeability and breakthrough time which are provided by the manufacturer/supplier of the gloves. Ensure gloves are suitable for the task which includes, but is not limited to, chemical compatibility, dexterity, operational conditions, user susceptibility, e.g., sensitization effects. Consider specific local conditions under which the product is used such as the danger of cuts and abrasion. Remove gloves with care to avoid skin contamination.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Eye protection:** Use equipment for eye protection tested and approved under government NIOSH standards.

## 9 Physical and chemical properties

### Information on basic physical and chemical properties

#### General Information

#### Appearance:

<b>Form:</b>	Fluid
<b>Color:</b>	Colorless
<b>Odor:</b>	Not determined
<b>Odor threshold:</b>	Not determined.

#### Change in condition

<b>Melting point/Melting range:</b>	18.45 °C (65.2 °F)
<b>Boiling point/Boiling range:</b>	Undetermined.
<b>Flash point:</b>	Not applicable.

**Flammability (solid, gaseous):** Not applicable.

**Auto igniting:** 270 °C (518 °F)

**Decomposition temperature:** Not determined.

**Ignition temperature:** Product is not selfigniting.

**Danger of explosion:** Product does not present an explosion hazard.

(Contd. on page 5)

US

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/11/2024

Reviewed on 01/10/2024

Trade name: HaloTag® Alexa Fluor® 660 Ligand

(Contd. of page 4)

**Explosion limits:**

**Lower:** Not determined.  
**Upper:** Not determined.  
**Vapor pressure at 20 °C (68 °F):** 2.5 hPa (1.9 mm Hg)

**Density at 20 °C (68 °F):** 1.1 g/cm<sup>3</sup> (9.1795 lbs/gal)

**Relative density** Not determined.

**Vapor density** Not determined.

**Evaporation rate** Not determined.

**Solubility in / Miscibility with**

**Water:** Fully miscible.

**Partition coefficient (n-octanol/water):** Not determined.

**Viscosity:**

**Dynamic:** Not determined.

**Kinematic:** Not determined.

**Solvent separation test**

**Organic solvents:** 99.7 %

**VOC content:** 99.66 %

**Other information** No further relevant information available.

\*

## 10 Stability and reactivity

**Reactivity** No further relevant information available.

**Chemical stability**

**Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

**Possibility of hazardous reactions** No dangerous reactions known.

**Conditions to avoid** No further relevant information available.

**Incompatible materials:**

Oxidizing agents

Strong acids

Strong reducing agents

**Hazardous decomposition products:** No dangerous decomposition products known.

\*

## 11 Toxicological information

**Information on toxicological effects****Acute toxicity:**

**LD/LC50 values that are relevant for classification:** No data available

**Primary irritant effect:**

**on the skin:** Causes skin irritation.

**on the eye:** No data available.

**Sensitization:**

**In case of skin contact:** not sensitising

**In case of inhalation:** not sensitising

**Additional toxicological information:** Harmful

**Carcinogenic categories**

**IARC (International Agency for Research on Cancer)**

None of the ingredients are listed.

(Contd. on page 6)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/11/2024

Reviewed on 01/10/2024

Trade name: HaloTag® Alexa Fluor® 660 Ligand

(Contd. of page 5)

**NTP (National Toxicology Program)**

None of the ingredients are listed.

**OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients are listed.

## 12 Ecological information

**Toxicity****Aquatic toxicity:** Not harmful to the aquatic environment**Persistence and degradability**

Not available

No further relevant information available.

**Bioaccumulative potential**

Not known

No further relevant information available.

**Mobility in soil** No further relevant information available.**Ecotoxicological effects:****Remark:** Not available**Additional ecological information:****General notes:** No data available.**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**Other adverse effects** No further relevant information available.

## 13 Disposal considerations

**Waste treatment methods****Recommendation:**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: Handling and Storage and Section 8: Exposure Control/Personal Protection for additional handling information and protection of employees.

**Uncleaned packagings:****Recommendation:** Disposal must be made according to official regulations.**Recommended cleansing agent:** Water, if necessary with cleansing agents.

## 14 Transport information

**UN-Number**

Not hazardous for transportation

**DOT, ADR, ADN, IMDG, IATA**

Not applicable

**UN proper shipping name**

None

**DOT, ADR, ADN, IMDG, IATA**

Not applicable

**Transport hazard class(es)**

None

**DOT, ADR, ADN, IMDG, IATA****Class**

Not applicable

**Packing group**

None

(Contd. on page 7)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 01/11/2024

Reviewed on 01/10/2024

Trade name: HaloTag® Alexa Fluor® 660 Ligand

(Contd. of page 6)

DOT, ADR, IMDG, IATA Not applicable

Environmental hazards:

Marine pollutant: No

Special precautions for user Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

UN "Model Regulation": Not applicable

## 15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture  
Sara

Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

TSCA (Toxic Substances Control Act) Inventory:

67-68-5 dimethyl sulfoxide

ACTIVE

Hazardous Air Pollutants

None of the ingredients are listed.

Proposition 65

Chemicals known to cause cancer:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

New Jersey Right-to-Know List:

67-68-5 dimethyl sulfoxide

Pennsylvania Right-to-Know List:

None of the ingredients are listed.

Carcinogenicity categories

EPA (Environmental Protection Agency)

None of the ingredients are listed.

TLV (Threshold Limit Value)

None of the ingredients are listed.

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Signal word Warning

(Contd. on page 8)

US

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 01/11/2024

Reviewed on 01/10/2024

Trade name: HaloTag® Alexa Fluor® 660 Ligand

(Contd. of page 7)

**Hazard-determining components of labeling:**

dimethyl sulfoxide

**Hazard statements**

Harmful if swallowed or in contact with skin.

**Precautionary statements**

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves / protective clothing.

If swallowed: Call a poison center/doctor if you feel unwell.

If on skin: Wash with plenty of water.

Rinse mouth.

Take off contaminated clothing and wash it before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Chemical safety assessment****Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

\*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Department issuing SDS:**

Promega Corporation

Chemical Regulatory Department

2800 Woods Hollow Road

Madison, WI

Ph: (608) 274-4330

chemicalregulatory@promega.com

**Contact:****Date of preparation / last revision** 01/11/2024**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety &amp; Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Toxicity - Oral 4: Acute toxicity – Category 4