

10/14/2022

Kit Components

Product code	Description
G1915	HaloLink® Resin, 25ml
Components:	
G631	HaloLink™ Resin II Slurry In Ethanol

Safety Data Sheet
acc. to OSHA HCS

Printing date 10/14/2022

Reviewed on 09/01/2022

1 Identification**Product identifier****Trade name:** HaloLink™ Resin II Slurry In Ethanol**Article number:** G63I**Application of the substance / the mixture** For Laboratory Use**Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

Promega Corporation

2800 Woods Hollow Road

Madison, WI 53711

U.S.A.

1-800-356-9526 or (608)-274-4330

Information department: SDS author: chemicalregulatory@promega.com**Emergency telephone number:**

For Chemical Emergency Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300

Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2 Hazard(s) identification**Classification of the substance or mixture**

GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.

Label elements**GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).**Hazard pictograms**

GHS02

Signal word Danger**Hazard statements**

Highly flammable liquid and vapor.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/14/2022

Reviewed on 09/01/2022

Trade name: HaloLink™ Resin II Slurry In Ethanol

(Contd. of page 1)

*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**In case of fire: Use CO2, powder or water spray to extinguish.**Store in a well-ventilated place. Keep cool.**Dispose of contents/container in accordance with local/regional/national/international regulations.***Classification system:****NFPA ratings (scale 0 - 4)**

Health = 0

Fire = 3

Reactivity = 0

HMIS-ratings (scale 0 - 4)

Health = 0

Fire = 3

Reactivity = 0

OSHA Hazard Overview (Criteria according to 29CFR1910.1200): Flammable**Primary route(s) of entry:** Inhalation**Target Organ(s):**

May cause Liver damage (Hepatotoxin)

May affect Nervous system (Neurotoxin)

Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures**Description:**

The product is made up of a mixture of hazardous and non-hazardous components. The exact concentration percentages and components name may be withheld as a Promega Corp. trade secret.

Dangerous components:

64-17-5 ethanol

15-20%

Additional information: For the wording of the listed risk phrases refer to section 15.

4 First-aid measures

Description of first aid measures**General information:** Immediately remove any clothing soiled by the product.**After inhalation:** If the patient feels unwell or is concerned, obtain medical advice.**After skin contact:** Generally the product does not irritate the skin.**After eye contact:** Rinse opened eye for several minutes under running water.**After swallowing:** If the patient feels unwell or is concerned, obtain medical advice.**Information for doctor:****Most important symptoms and effects, both acute and delayed**

Headache

Dizziness

Nausea

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/14/2022

Reviewed on 09/01/2022

Trade name: HaloLink™ Resin II Slurry In Ethanol

(Contd. of page 2)

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents: Use fire fighting measures that suit the environment.

Special hazards arising from the substance or mixture

None known

No further relevant information available.

Advice for firefighters In the case of fire, wear respiratory protective equipment and chemical protective suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources

Wear protective clothing.

Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Use only in well ventilated areas.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Specific end use(s) No further relevant information available.

US

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/14/2022

Reviewed on 09/01/2022

Trade name: HaloLink™ Resin II Slurry In Ethanol

(Contd. of page 3)

8 Exposure controls/personal protection

Control parameters

Components with limit values that require monitoring at the workplace:

64-17-5 ethanol

PEL Long-term value: 1900 mg/m³, 1000 ppm

REL Long-term value: 1900 mg/m³, 1000 ppm

TLV Short-term value: 1000 ppm

A3

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands: Not required.

Material of gloves

Gloves impermeable to the specific chemical substance.

Please observe the instructions regarding permeability and breakthrough time which are provided by the manufacturer/supplier of the gloves. Ensure gloves are suitable for the task which includes, but is not limited to, chemical compatibility, dexterity, operational conditions, user susceptibility, e.g., sensitization effects. Consider specific local conditions under which the product is used such as the danger of cuts and abrasion. Remove gloves with care to avoid skin contamination.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Eye protection:

Safety glasses

Use equipment for eye protection tested and approved under government NIOSH standards.

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form:	Fluid
Color:	Colorless
Odor:	Alcohol-like
Odor threshold:	Not determined.

Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	78 °C (172.4 °F)
Flash point:	14 °C (57.2 °F)

Flammability (solid, gaseous): Highly flammable.

Ignition temperature: 425 °C (797 °F)

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/14/2022

Reviewed on 09/01/2022

Trade name: HaloLink™ Resin II Slurry In Ethanol

(Contd. of page 4)

Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard. Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Explosion limits:	
Lower:	3.5 Vol %
Upper:	15 Vol %
Vapor pressure at 20 °C (68 °F):	59 hPa (44.3 mm Hg)
Density at 20 °C (68 °F):	0.975 g/cm ³ (8.13638 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.
Partition coefficient (n-octanol/water):	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent separation test	
Organic solvents:	18.8 %
Water:	56.3 %
VOC content:	18.75 %
Solids content:	25.0 %
Other information	No further relevant information available.

10 Stability and reactivity

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification: No data available

Primary irritant effect:

on the skin: Causes skin irritation.

on the eye: No data available.

Sensitization:

In case of skin contact: not sensitising

In case of inhalation: not sensitising

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/14/2022

Reviewed on 09/01/2022

Trade name: HaloLink™ Resin II Slurry In Ethanol

(Contd. of page 5)

Additional toxicological information:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

Carcinogenic categories**IARC (International Agency for Research on Cancer)**

64-17-5 ethanol

I

NTP (National Toxicology Program)

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

Toxicity**Aquatic toxicity:** Not harmful to the aquatic environment**Persistence and degradability**

Not available

No further relevant information available.

Bioaccumulative potential

Not known

No further relevant information available.

Mobility in soil No further relevant information available.**Ecotoxicological effects:****Remark:** Not available**Additional ecological information:****General notes:** No data available.**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**Other adverse effects** No further relevant information available.

13 Disposal considerations

Waste treatment methods**Recommendation:**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: Handling and Storage and Section 8: Exposure Control/Personal Protection for additional handling information and protection of employees.

Uncleaned packagings:**Recommendation:** Disposal must be made according to official regulations.**Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

UN-Number**DOT, ADR, IMDG, IATA**

UN1170

(Contd. on page 7)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/14/2022

Reviewed on 09/01/2022

Trade name: HaloLink™ Resin II Slurry In Ethanol

(Contd. of page 6)

UN proper shipping name**DOT**

Ethanol

ADR

1170 ETHANOL (ETHYL ALCOHOL)

IMDG

ETHANOL (ETHYL ALCOHOL)

IATA

ETHANOL

Transport hazard class(es)**DOT****Class**

3 Flammable liquids

Label

3

ADR**Class**

3 (F1) Flammable liquids

Label

3

IMDG, IATA**Class**

3 Flammable liquids

Label

3

Packing group**DOT, ADR, IMDG, IATA**

II

Environmental hazards:**Marine pollutant:**

No

Special precautions for user

Warning: Flammable liquids

Hazard identification number (Kemler code): 33**EMS Number:**

F-E,S-D

Stowage Category

A

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

Transport/Additional information:**ADR****Exempted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/14/2022

Reviewed on 09/01/2022

Trade name: HaloLink™ Resin II Slurry In Ethanol

(Contd. of page 7)

IMDG**Limited quantities (LQ)**

1L

Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

UN "Model Regulation":

UN 1170 ETHANOL (ETHYL ALCOHOL), 3, II

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
Sara

Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

TSCA (Toxic Substances Control Act) Inventory:

64-17-5 ethanol

Hazardous Air Pollutants

None of the ingredients are listed.

Proposition 65**Chemicals known to cause cancer:**

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

Chemicals known to cause developmental toxicity:

64-17-5 ethanol

New Jersey Right-to-Know List:

64-17-5 ethanol

Pennsylvania Right-to-Know List:

64-17-5 ethanol

Carcinogenicity categories**EPA (Environmental Protection Agency)**

None of the ingredients are listed.

TLV (Threshold Limit Value)

64-17-5 ethanol

A3

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).**Signal word** Danger**Hazard statements**

Highly flammable liquid and vapor.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/14/2022

Reviewed on 09/01/2022

Trade name: **HaloLink™ Resin II Slurry In Ethanol**

(Contd. of page 8)

Precautionary statements*Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Keep container tightly closed.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.**Wear protective gloves/protective clothing/eye protection/face protection.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**In case of fire: Use CO2, powder or water spray to extinguish.**Store in a well-ventilated place. Keep cool.**Dispose of contents/container in accordance with local/regional/national/international regulations.***Chemical safety assessment****Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS:

Promega Corporation

Chemical Regulatory Department

2800 Woods Hollow Road

Madison, WI

Ph: (608) 274-4330

chemicalregulatory@promega.com

Contact:**Date of preparation / last revision** 10/14/2022**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2