

01/11/2024

Kit Components

Product code	Description
G1001	HaloTag® Alexa Fluor® 488 Ligand
Components:	
G100A	HaloTag® Alexa Fluor® 488 Ligand

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/11/2024

Reviewed on 12/28/2023

1 Identification**Product identifier****Trade name:** HaloTag® Alexa Fluor® 488 Ligand**Article number:** G100A**Application of the substance / the mixture** For Laboratory Use**Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

Promega Corporation

2800 Woods Hollow Road

Madison, WI 53711

U.S.A.

1-800-356-9526 or (608)-274-4330

Information department: SDS author: chemicalregulatory@promega.com**Emergency telephone number:**

For Chemical Emergency Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300

Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2 Hazard(s) identification**Classification of the substance or mixture**

GHS07

Acute Toxicity - Dermal 4 H312 Harmful in contact with skin.

Flammable Liquids 4 H227 Combustible liquid.

Label elements**GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).**Hazard pictograms**

GHS07

Signal word Warning**Hazard-determining components of labeling:**

dimethyl sulfoxide

Hazard statements

Combustible liquid.

Harmful in contact with skin.

Precautionary statements

Keep away from flames and hot surfaces. – No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/11/2024

Reviewed on 12/28/2023

Trade name: **HaloTag® Alexa Fluor® 488 Ligand**

(Contd. of page 1)

If on skin: Wash with plenty of water.
 Call a poison center/doctor if you feel unwell.
 Take off contaminated clothing and wash it before reuse.
 In case of fire: Use CO₂, powder or water spray to extinguish.
 Store in a well-ventilated place. Keep cool.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:**NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 2

Reactivity = 0

HMIS-ratings (scale 0 - 4)

Health = 1

Fire = 2

Reactivity = 0

OSHA Hazard Overview (Criteria according to 29CFR1910.1200): Combustible**Primary route(s) of entry:** Dermal**Target Organ(s):**

Dermal hazard (Cutaneous hazard)

Risk of damage to eyes

Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures**Description:**

The product is made up of a mixture of hazardous and non-hazardous components. The exact concentration percentages and components name may be withheld as a Promega Corp. trade secret.

Dangerous components:

67-68-5 dimethyl sulfoxide

75-100%

Additional information: For the wording of the listed risk phrases refer to section 15.

4 First-aid measures

Description of first aid measures**General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation: If the patient feels unwell or is concerned, obtain medical advice.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Immediately call a doctor.

Information for doctor:

Most important symptoms and effects, both acute and delayed

None

No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/11/2024

Reviewed on 12/28/2023

Trade name: HaloTag® Alexa Fluor® 488 Ligand

(Contd. of page 2)

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents: Use fire fighting measures that suit the environment.

Special hazards arising from the substance or mixture

None known

No further relevant information available.

Advice for firefighters In the case of fire, wear respiratory protective equipment and chemical protective suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Wear protective equipment. Keep unprotected persons away.

Wear protective clothing.

Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Dilute with plenty of water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling No special precautions are necessary if used correctly.

Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Do not store below -20°C. Protected from light.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep receptacle tightly sealed.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Control parameters

Components with limit values that require monitoring at the workplace:

67-68-5 dimethyl sulfoxide

WEEL Long-term value: 250 ppm

Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/11/2024

Reviewed on 12/28/2023

Trade name: HaloTag® Alexa Fluor® 488 Ligand

(Contd. of page 3)

Exposure controls**Personal protective equipment:****General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Clean skin thoroughly immediately after handling the product.

Breathing equipment: Not required.**Protection of hands:**

Select the glove material considering penetration time, rate of diffusion and degradation time.

Material of gloves

Gloves impermeable to the specific chemical substance.

Please observe the instructions regarding permeability and breakthrough time which are provided by the manufacturer/supplier of the gloves. Ensure gloves are suitable for the task which includes, but is not limited to, chemical compatibility, dexterity, operational conditions, user susceptibility, e.g., sensitization effects. Consider specific local conditions under which the product is used such as the danger of cuts and abrasion. Remove gloves with care to avoid skin contamination.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Eye protection:

Safety glasses

Use equipment for eye protection tested and approved under government NIOSH standards.

9 Physical and chemical properties

Information on basic physical and chemical properties**General Information****Appearance:**

Form:	Fluid
Color:	Colorless
Odor:	Not determined
Odor threshold:	Not determined.

Change in condition

Melting point/Melting range:	18.45 °C (65.2 °F)
Boiling point/Boiling range:	189 °C (372.2 °F)
Flash point:	87 °C (188.6 °F)

Flammability (solid, gaseous): Not applicable.**Auto igniting:** 270 °C (518 °F)**Decomposition temperature:** Not determined.**Ignition temperature:** Product is not selfigniting.**Danger of explosion:** Product does not present an explosion hazard.**Explosion limits:**

Lower:	1.8 Vol %
Upper:	Zers Vol %
Vapor pressure at 20 °C (68 °F):	2.5 hPa (1.9 mm Hg)

Density at 20 °C (68 °F): 1.1 g/cm³ (9.1795 lbs/gal)**Relative density** Not determined.**Vapor density** Not determined.

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/11/2024

Reviewed on 12/28/2023

Trade name: HaloTag® Alexa Fluor® 488 Ligand

(Contd. of page 4)

Evaporation rate Not determined.

Solubility in / Miscibility with

Water: Fully miscible.

Partition coefficient (n-octanol/water): Not determined.

Viscosity:

Dynamic at 20 °C (68 °F): 198 mPas

Kinematic: Not determined.

Solvent separation test

Organic solvents: 99.9 %

VOC content: 99.90 %

Solids content: 0.1 %

Other information No further relevant information available.

10 Stability and reactivity

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials:

Oxidizing agents

Strong acids

Strong reducing agents

Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification: No data available

Primary irritant effect:

on the skin: Causes skin irritation.

on the eye: No data available.

Sensitization:

In case of skin contact: not sensitising

In case of inhalation: not sensitising

Additional toxicological information: Harmful

Carcinogenic categories

IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

NTP (National Toxicology Program)

None of the ingredients are listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/11/2024

Reviewed on 12/28/2023

Trade name: HaloTag® Alexa Fluor® 488 Ligand

(Contd. of page 5)

12 Ecological information

Toxicity

Aquatic toxicity: Not harmful to the aquatic environment

Persistence and degradability

Not available

No further relevant information available.

Bioaccumulative potential

Not known

No further relevant information available.

Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark: Not available

Additional ecological information:

General notes: Not available.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

Recommendation:

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: Handling and Storage and Section 8: Exposure Control/Personal Protection for additional handling information and protection of employees.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number	Not hazardous for transportation
DOT, ADR, ADN, IMDG, IATA	Not applicable
UN proper shipping name	None
DOT, ADR, ADN, IMDG, IATA	Not applicable
Transport hazard class(es)	None
DOT, ADR, ADN, IMDG, IATA	
Class	Not applicable
Packing group	None
DOT, ADR, IMDG, IATA	Not applicable
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Not applicable.

(Contd. on page 7)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/11/2024

Reviewed on 12/28/2023

Trade name: HaloTag® Alexa Fluor® 488 Ligand

(Contd. of page 6)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

UN "Model Regulation": Not applicable

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
Sara

Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

TSCA (Toxic Substances Control Act) Inventory:

67-68-5 dimethyl sulfoxide

ACTIVE

Hazardous Air Pollutants

None of the ingredients are listed.

Proposition 65

Chemicals known to cause cancer:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

New Jersey Right-to-Know List:

67-68-5 dimethyl sulfoxide

Pennsylvania Right-to-Know List:

None of the ingredients are listed.

Carcinogenicity categories

EPA (Environmental Protection Agency)

None of the ingredients are listed.

TLV (Threshold Limit Value)

None of the ingredients are listed.

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
Signal word Warning

Hazard-determining components of labeling:

dimethyl sulfoxide

Hazard statements

Combustible liquid.

Harmful in contact with skin.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/11/2024

Reviewed on 12/28/2023

Trade name: HaloTag® Alexa Fluor® 488 Ligand

(Contd. of page 7)

Precautionary statements*Keep away from flames and hot surfaces. – No smoking.**Wear protective gloves/protective clothing/eye protection/face protection.**If on skin: Wash with plenty of water.**Call a poison center/doctor if you feel unwell.**Take off contaminated clothing and wash it before reuse.**In case of fire: Use CO2, powder or water spray to extinguish.**Store in a well-ventilated place. Keep cool.**Dispose of contents/container in accordance with local/regional/national/international regulations.***Chemical safety assessment****Water hazard class:** Generally not hazardous for water.**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS:

Promega Corporation

Chemical Regulatory Department

2800 Woods Hollow Road

Madison, WI

Ph: (608) 274-4330

chemicalregulatory@promega.com

Contact:**Date of preparation / last revision** 01/11/2024**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 4: Flammable liquids – Category 4

Acute Toxicity - Dermal 4: Acute toxicity – Category 4